



Part# TW-2



Part# TW-1.5



Part# TW-1.25



Part# TW-1

“Thread Wright” Calibration Tool

The “Thread Wright” is a tool used to calibrate the correct thread depth on any pipe threading machine with an adjustable die head. The traditional trial and error method: threading a pipe, checking the depth by threading on a fitting to get approximately three turns, and if the threads are too shallow or too deep you have to adjust the depth and repeat the pro-

cess sometimes taking five to fifteen minutes to get them set correctly. The “Thread Wright” cuts the time down to seconds. You simply place the “Thread Wright” between the dies and adjust the dies down till they touch the surface of the “Thread Wright”, lock down the adjustment lever, push the release lever and remove the “Thread Wright”. Now you are ready to thread a piece of pipe and you will

get the correct thread depth for approximately three turns on the fitting every time.
Any company that threads pipe can increase their bottom line by using the “Thread Wright.” A small fabrication shop tracked how much time their employee’s spent calibrating dies. They spent approximately \$4500 per year per man calibrating dies, or

There is also the added benefit of the consistency of the thread depth which will reduce the chance of leaks in the field. To go back to a job and fix a leak costs a minimum of \$500.00 in time and lost productivity, not including any equipment such as lifts needed to reach the leak or damage to finished surfaces.

The “Thread Wright” is a must have tool for any company that threads pipe. It will save money and time and increase the quality and consistency of the thread depth.

BENEFITS USING THE “THREAD WRIGHT”

- Reduces the time spent calibrating dies
- Saves money and increases productivity
- More consistent thread depth

cess sometimes taking five to fifteen minutes to get them set correctly. The “Thread Wright” cuts the time down to seconds. You simply place the “Thread Wright” between the dies and adjust the dies down till they touch the surface of the “Thread Wright”, lock down the adjustment lever, push the release lever and remove the “Thread Wright”. Now you are ready to thread a piece of pipe and you will

\$2.16 per hour based on a 40 hour week. If that employee makes \$15.00 per hour, then he would spend 8.64 minutes of every hour adjusting dies. Reduce that time to one minute, or \$.25 per hour or \$520.00 per year. By using the “Thread Wright” this fabrication shop could save almost \$4000 per year, per man plus the added 7.64 minutes per hour or 264 hours per year of productivity.



Part# TW-1.5

Disclaimer: All benefits are dependent on the threading machine and die head being in good working condition.

111 Byrd Lane
Dandridge, TN 37725



www.hydrostatictestpump.net